



DIN 84 Винт с цилиндрической головкой и прямым шлицем.

Таблица характеристик:

d	M2	M2,5	M3	M3,5	M4	M5	M6	M8	M10	M12
dk	3,8	4,5	5,5	6	7	8,5	10	13	16	18
k	1,3	1,6	2	2,4	2,6	3,3	3,9	5	6	7
n	0,5	0,6	0,8	1	1,2	1,2	1,6	2	2,5	
t min	0,6	0,7	0,85	1	1,1	1,3	1,6	2	2,4	
3	v	v	v							
4	v	v	v		v					
5	v	v	v	v	v	v				
6	v	v	v	v	v	v	v			
8	v	v	v	v	v	v	v			
10	v	v	v	v	v	v	v	v		
12	v	v	v	v	v	v	v	v	v	
14	v	v	v	v	v	v	v	v	v	
16	v	v	v	v	v	v	v	v	v	
18	v	v	v	v	v	v	v	v	v	
20	v	v	v	v	v	v	v	v	v	v
22		v	v	v	v	v	v	v	v	
25	v	v	v	v	v	v	v	v	v	v
28		v	v	v	v	v	v	v	v	
30	v	v	v	v	v	v	v	v	v	v
35			v	v	v	v	v	v	v	v
40			v	v	v	v	v	v	v	v
45			v	v	v	v	v	v	v	v
50			v	v	v	v	v	v	v	v
55			v	v	v	v	v	v	v	v
60			v	v	v	v	v	v	v	v
65			v	v	v	v	v	v	v	
70			v	v	v	v	v	v	v	v
75			v	v	v	v	v	v	v	
80			v		v	v	v	v	v	v
90			v		v	v	v	v	v	
100			v		v	v	v	v	v	