



DIN 912 Винт с цилиндрической головкой и внутренним шестигранником.

Таблица характеристик:

d	M8	M10	M10	M12	M12	M14	M16	M20	M20	M24	M24	M27	M30	M36	M42	M48
	1	1	1.25	1.25	1.5	1.5	1.5	1.5	2	1.5	2	2	2	3	3	3
b	28	32	32	36	36	40	44	52	52	56	56	66	72	84	96	108
dk	13	15	15	18	18	21	24	30	30	33	33	40	45	54	63	72
k	8	10	10	12	12	14	16	20	20	22	22	27	30	36	42	48
s	6	8	8	10	10	12	14	17	17	17	17	19	22	27	32	35
t	4	5	5	6	6	7	8	10	10	11	11	13.5	15.5	19	24	28
16	v	v	v													
20	v	v	v	v	v											
25	v	v	v	v	v	v	v									
30	v	v	v	v	v	v	v	v	v							
35	v	v	v	v	v	v	v									
40	v	v	v	v	v	v	v	v				v	v			
45	v	v	v	v	v	v	v	v				v	v			
50	v	v	v	v	v	v	v	v	v	v	v	v	v			
55	v	v	v	v	v	v	v	v		v	v	v	v			
60	v	v	v	v	v	v	v	v	v	v	v	v	v			
65	v	v	v	v	v	v	v	v	v		v	v	v			
70	v	v	v	v	v	v	v	v	v	v	v	v	v			
80	v	v	v	v	v	v	v	v	v	v	v	v	v			
90	v	v	v	v	v	v	v	v	v	v	v	v	v			
100	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
110	v	v	v	v	v	v	v	v	v	v	v	v	v			
120	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
130		v	v		v	v	v	v	v	v	v	v	v	v	v	
140		v	v		v	v	v	v	v	v	v	v	v	v	v	v
150			v	v	v	v	v	v	v	v	v	v	v	v	v	
160			v	v	v	v	v	v	v	v	v	v	v	v	v	v
170			v		v	v	v			v		v	v			
180					v	v	v	v		v	v	v	v	v	v	v
200				v		v	v	v	v	v		v	v	v	v	v
220												v	v	v	v	v
240												v	v	v	v	v
260												v	v	v		v
300												v	v	v	v	v